

SPARTAN SPZ-BL

Industrial LED BL Linear



Key Features

- Linear LED luminaire for the conventional vapor tight category
- Two lumen output levels
- Suitable for high ambient temperature operation
- Multiple mounting options
- 3/4" NPT entries on 3 sides
- Thru-wiring: multiple units can be daisy-chained on a single electrical circuit
- Optional dimming knob (120VAC and Dry/Damp Locations only)
- Vented and IP66 sealed enclosure for enhanced reliability
- Industrial grade housing designed to withstand vibration and impact
- Certified for use in Marine Locations (UL 1598A); marine-grade copper-free aluminum construction with stainless steel mounting hardware
- Triple layer corrosion protection: Chromate conversion coating, epoxy powder coat primer, super-durable polyester powder top-coat
- Glare reduction lens for enhanced visual comfort
- All sub-assemblies are field serviceable and replaceable




Technical Specifications / Maximum Ratings

HOUSING	Die-cast Powder Coated Aluminum w/ Polycarbonate Lens
MOUNTING	SEE PAGE 2-4 FOR MOUNTING OPTIONS
INPUT VOLTAGE	AC: 120-277VAC** HV: 347VAC (50/60 Hz)
RATED POWER	BL20: 17.5W BL40: 37W
TYPICAL CURRENT	BL40: 120VAC, 0.30A 277VAC, 0.13A 347VAC, 0.10A BL20: 120VAC, 0.14A 277VAC, 0.06A 347VAC, 0.05A
CONNECTIONS	3 x 3/4" NPT Daisy Chain Wiring
TEMPERATURE RANGE	-50°C to +65°C (Case ~30°C above ambient)
CERTIFICATIONS	Certified to UL 1598, UL 1598A & UL 8750; CSA 22.2 No. 250.0; CSA 22.2 No. 250.13
INGRESS PROTECTION	IP66 Suitable for wet locations. Marine Outside type (Salt water).
COLOUR TEMP RANGE	50: 5000K Special Order: 2700-6500K
CRI VALUE (MIN)	50: 70
EFFICACY (5000k)	BL20: 145lm/w BL40: 130 lm/w (5000K CCT, 120VAC typical power)
TOTAL LUMENS	BL20: 2540 BL40: 4475
PROJECTED SYSTEM LIFE	>100,000hrs
WEIGHT	2.9 kg (6.4 lbs)

* The ambient temperature during lifetime, lumen and chromaticity determination is 25°C ± 1°C

** Units with dimming knob and/or corded plug are rated for 120VAC and IP20 (suitable for dry/damp locations) only.

Dimensions




Warranty


Five (5) year limited warranty to the original purchaser. The warranty covers defects in materials and workmanship under normal use and service.

Please contact Raytec for more information.

Photometrics




Dimming




- Driver will source a maximum of 200uA for control needs
- Controller must sink current from the 0-10V control leads

Mounting Options (All mounting accessories must be ordered separately)

PENDANT/CONDUIT MOUNT (SPX-BKT-R-CC) : 3.0 kg | 6.6 lbs *Not including conduit*
(Direct connection of BL luminaire to hanging conduit)




SURFACE MOUNT (SPX-BKT-BL-SM) : 3.2 kg | 7.0 lbs (Optional accessory)




Mounting Options (Cont.)


WALL MOUNT (SPX-BKT-BL-WM) : 3.1 kg | 6.8 lbs (Optional accessory)



ADJUSTABLE YOKE MOUNT (SPX-BKT-BL-YM): 3.3 kg | 7.2 lbs (Optional accessory)




HOOK MOUNT (SPX-BKT-BL-HK): 3.2kg | 7.0lbs (Optional accessory)




Mounting Options (Cont.)

TUBE CLAMP MOUNT (SPX-BKT-BL-TC): 3.2 kg | 7.0 lbs

(Optional accessory)



STRAP MOUNTING: 3.1 kg | 6.8 lbs (Optional accessory)



P/N	Qty	Description
STS12	2	Stainless steel tube clamp, ts 9 3/8" to 12" tubing diameter
STS9	2	Stainless steel tube clamp, ts 7 1/8" to 9 3/4" tubing diameter
STS8	2	Stainless steel tube clamp, ts 5 5/8" to 8 1/4" tubing diameter
STS6	2	Stainless steel tube clamp, ts 4 1/8" to 6 3/4" tubing diameter
STS5	2	Stainless steel tube clamp, ts 3 5/8" to 6 1/4" tubing diameter
STS4	2	Stainless steel tube clamp, ts 3 5/16" to 4 1/4" tubing diameter
STS3	2	Stainless steel tube clamp, ts 2 9/16" to 3 1/4" tubing diameter

Product Code Builder

Example Order Reference: SPZ-BL40-5K-120120-GY-AC-GN-DS

Classification*	Model	Colour Temp*	Finish*	Input Power	Location	Options
SPZ	BL20	50 – 5000K (70CRI)	GY - Grey	AC – 120-277VAC	GN- General Location	GW – Glass Window in Stainless Frame
	BL40			HV – 347-480VAC		DS – Dimming Switch
						DP – Dimming Switch & 6' Nema 5-15 Corded Plug
						515P – 6' Nema 5-15 Corded Plug

*Hazardous variants available

*Other options available

*Custom finishes available. Please contact for details.²

Accessories (Sold Separately)

Accessory	Part Number
Surface Mount ^{1,2}	SPX-BKT-BL-SM-GY
Wall Mount ^{1,2}	SPX-BKT-BL-WM-GY
Pendant Conduit Mount	SPX-BKT-BL-R-CC-GY
Yoke Mount ^{1,2}	SPX-BKT-BL-YM-GY
Hook Mount	SPX-BKT-BL-HK-GY
Tube Clamp Mount ^{1,2}	SPX-BKT-BL-TC-GY
SS Straps ¹	SPX-BKT-BL-STS-GY

Bespoke colour options available, contact Raytec.

NOTES:

1. Stainless steel mounting accessories no colour code standard i.e BL-SM.
2. Minimum order quantities, additional costs and lead times may apply
3. Units with dimming knob and/or corded plug are rated for 120VAC and IP20 (suitable for dry/damp locations) only.
4. Mounting hardware may be ordered with luminaire or as stand-alone hardware kits.