




EU Type Examination Certificate CML 18ATEX3161 Issue 2

- 1 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- 2 Equipment **HP Spartan LED Luminaire (for dust atmospheres)**
- 3 Manufacturer **Raytec Ltd.**
- 4 Address Unit 15 Wansbeck Business Park
Rotary Parkway
Ashington
Northumberland
NE63 8QW, UK
- 5 The equipment is specified in the description of this certificate and the documents to which it refers.
- 6 CML B.V., Chamber of Commerce No 67386717, Koopvaardijweg 32, 4906CV Oosterhout, The Netherlands, Notified Body Number 2776, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 12.
- 7 If an 'X' suffix appears after the certificate number, it indicates that the equipment is subject to conditions of safe use (affecting correct installation or safe use). These are specified in Section 14.
- 8 This EU Type Examination certificate relates only to the design and construction of the specified equipment or component. Further requirements of Directive 2014/34/EU Article 13 apply to the manufacture of the equipment or component and are separately certified.
- 9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:

EN IEC 60079-0:2018 EN 60079-31:2014
- 10 The equipment shall be marked with the following:



II 2 D

Ex tb IIIC T104°C Db

Ta = -50°C to +50°C



This certificate shall only be copied
in its entirety and without change

www.CMLEx.com

Ben Trafford
Certification Officer



**CML 18ATEX3161
Issue 2**

11 Description

The combined PSU and JB assembly consists of two separate dust protected enclosures, one containing LED Driver circuits and the other containing suitably certified Ex component terminals, for connection of internal and field wiring using suitably certified cable glands. The two enclosures are separated using a suitably certified bushing.

The above combined assembly is mounted to the dust protected LED compartment, with the wiring from the JB compartment connected to the LED assemblies.

The units have an environmental rating of IP 66.

A maximum of two cable entries can be supplied with each luminaire. Suitably certified cable entries may be various thread types up to a maximum diameter of 25 mm.

The equipment is also marked with an ingress protection rating of IP67. An ingress protection rating of IPX7 has not been verified under the CML certification.

An optional self-adhesive anti-static film can be fitted over the glass externally.

Operating voltage may be 150-264V AC/DC or 110V-264V AC/DC with a maximum wattage of 300W.

Variation 1

This variation introduced the following modifications:

- i. To update and review the product against the latest editions of the standards.
- ii. To remove the type of protection 'op is' and standard IEC/EN 60079-28 from the certification.
- iii. To assess and confirm the toughened glass window assembly meets the high risk level impact energy (7J).
- iv. To amend the certification by including the latest component certification for the BK and MK series terminal blocks and remove the old versions.
- v. To transfer the ATEX certification from CML UK to CML B.V.
- vi. Clarification regarding the marked current rating.
- vii. Changes to the ingress protection rating specified on the marking and the addition of information to the product description, also relating to the marked IP rating.
- viii. The introduction of an alternative LED.

Variation 2

This variation introduced the following modifications:

- i. Minor changes to LED board

12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
0	24 Jul 2017	R1722A/00	Contributing report (for Zone 1/21 and 2/22 variants: CML 17ATEX1148 & CML 17ATEX4149).
	15 June 2018	R11782A/00	Contributing report (variation to Zone 1/21 and 2/22 variants: CML 17ATEX1148 & CML 17ATEX4149).
	15 June 2018	R11783A/00	Report for initial certificate for Zone 21 variant.



**CML 18ATEX3161
Issue 2**

1	27 Oct 2020	R13535A/00	Introduction of variation 1
2	24 May 2023	R16358A/00	Introduction of variation 2

Note: Drawings that describe the equipment or component are listed in the Annex.

13 Conditions of Manufacture

The following conditions are required of the manufacturing process for compliance with the certification.

- i. Where the product incorporates certified parts or safety critical components, the manufacturer of the product defined on this certificate shall continually monitor these parts/components for any modifications introduced by the manufacturer(s) of these constituent parts. If the manufacturer of any constituent part introduces any changes which affect the compliance of the certified product that is the subject of this certificate, the manufacturer is required to have this certificate updated.
- ii. The manufacturer shall fit only the certified Ex Components listed in the certification documentation and the manufacturer's instructions. All Special Conditions of Certification/ Special Conditions for Safe Use/ Schedule of Limitations shall be satisfied for each part fitted.
- iii. If the terminals or components are fitted with cables/wiring by the manufacturer; all cables/wires shall be suitable for rated voltage and current of each separate circuits and Ex Components to which they are connected.
- iv. The Line Bushing shall be suitable for a service temperature range of at least -50°C to +85°C.
- v. Where the LEDs are configured in a single string of 12 connected in series, only the XLamp LEDs are to be used.

14 Specific Conditions of Use (Special Conditions)

None.

Certificate Annex

Certificate Number CML 18ATEX3161
Equipment HP Spartan LED Luminaire (for dust atmospheres)
Manufacturer Raytec Ltd.



The following documents describe the equipment or component defined in this certificate:

Issue 0

Drawing No	Sheets	Rev	Approved date	Title
1050-SD-00034	1 to 4	B	15 June 2018	Spartan High Power LED Floodlight/Highbay
1050-SD-0001	1 to 5	A	15 June 2018	HPFL FMEA Dated 22-05-2017
1050-SD-0002	1 of 1	A	15 June 2018	HP Flood Protection circuit schematic
1050-SD-0003	1 of 1	A	15 June 2018	Protection circuit parts list
1050-SD-0006	1 of 1	A	15 June 2018	Wadco Bosse HP LED Luminaire Zone 1 nameplate

Issue 1

Drawing No	Sheets	Rev	Approved date	Title
1050-SD-00034	1 to 4	C	26 Oct 2020	Spartan High-Power LED Floodlight/Highbay

Note: Previously approved drawing number 1050-SD-0006 has been removed from the certification.

Issue 2

Drawing No	Sheets	Rev	Approved date	Title
1050-SD-00034	2 of 4	F	24 May 2023	SPARTAN HIGH POWER LED FLOODLIGHT/HIGHBAY
1050-SD-00034	3 of 4	E	24 May 2023	SPARTAN HIGH POWER LED FLOODLIGHT/HIGHBAY