

SPARTAN SPZ Street LED Zone 2/22 Street Luminaire



rayTEC



Energy Saving

With a low power consumption of 53W, and a high efficacy of 156lm/W, SPARTAN Street delivers significant energy savings and outstanding optical performance.



Easy to Install

SPARTAN Street weighs only 6.5kg and comes pre-terminated with a 12M outdoor, 3 core, cold resistant, PVC cable for quick and easy installation.



Ultra-Flexible

With an adjustable bracket that can be rotated 90°, the luminaire can be fixed to any column, bracket or pole in post top or side arm configuration.



Bespoke LED

Raytec are specialists in LEDs and all our products are designed around the LEDs with bespoke housing for optimum performance and reliability.

5 YEAR WARRANTY

All Raytec luminaires are provided with an industry leading 5 year warranty and have an expected useful life in excess of 10 years. See Warranty Statement for details.



Technical Specifications

Certification

ATEX Rating	ATEX, UKEX and IEC Ex rated for Gas and Dust
Hazardous Area Rating	Zone 2 (Gas), Zone 22 (Dust)
Certificates	IECEX CML 23.0094X, CML 23ATEX4285X, CML 23UKEX4286X
Gas	II 3 G Ex ec mc IIC T4 Gc Ta = -40 °C to +50 °C
Dust	II 3 D Ex tc IIIC T80°C Dc Ta = -40 °C to +50 °C

Electrical

Input	110-254VAC 50/60Hz
Power	53W
Termination	Supplied pre-terminated, with 12m of 3 core Outdoor Cold Resistant PVC Cable
Power Factor	>0.95


Optical

Beam Patterns	Perimeter/Pathway - PP1 Perimeter/Pathway - PP2 Perimeter/Pathway - PP3 Area - AR1
Lumen output on mains	Up to 8,300
LED type	Platinum Elite SMT LEDs
Number of LEDs	96
CRI	≥80
Colour Temperature	4000K


Mechanical

IP Rating	IP66
IK Rating	IK07
Temperature Range	-40°C to +50°C
Weight	6.5Kg
Enclosure	Marine grade aluminium epoxy powder coated, all external fasteners and brackets are marine grade stainless steel
Unit Colour	Silver (RAL 9006)
Installation Instructions	See document 1286-D-00002 at www.rayteclcd.com
Dimensions	See dimensional sketches
Mounting	Supplied with Integrated Spigot Mount with adjustable rotation
Spigot (pole) Diameter	Compatible with 76mm pole diameter (48mm & 60mm pole adaptors are available)

Light Distribution



Product Dimensions



Part Code Builder

SPARTAN Street Zone 2

Standard: Example - SPZ-SL96-4K-PP1				
Family	Model	CCT	Optic	POLE ADAPTOR
SPZ	SL96	4K	PP1	NOT STATED - Suits 76mm Pole
		Other colour options available - Contact Raytec	PP2	(60mm & 48mm Pole Adaptors are available)
			PP3	
			AR1	